

# HEAT PUMP

DEDICATED TO SMALL POOLS

**POOLEX**  
SUIVEZ L'EXPERT

## POOLEX NANO ACTION



$COP \geq 4.7$   
AIR 26°C WATER 26°C

$< 32dB^{**}$   
À 10 M

FOR POOL UNTIL  
**20** m<sup>3</sup>

**ULTRA  
COMPACT**

Power consumption  
**0,6kW**

 COP 4.7

Heating power  
**2,7kW**

\* COP above 4,75 based on Air 26°C, water 26°C, hygro 80% and certified by TÜV

\*\* Average noise 10m distance from heat pump

# HEAT PUMP

## DEDICATED TO SMALL POOLS

**POOLEX**  
**NANO**  
**ACTION**



**COP  $\geq 4.7$**   
AIR 26°C WATER 26°C

**< 32dB** \*\*  
AT 10 M

FOR POOL UNTIL  
**20** m<sup>3</sup>

**ULTRA  
COMPACT**

### Poolex Nano ACTION :

the heat pump specifically developed for small swimming pools.

With its TOSHIBA compressor, the Nano Action ensures a hot pool temperature, throughout the summer.

Plug it into a conventional electrical outlet, and heat your pool above ground in a few hours.

Its unique design and small dimensions allow the Poolex Nano Action to integrate next to any pool.

The performance of a Poolex at the best price.



Certification



TÜV



MATERIAL DURABLE



SILENT EFFICIENCY



OZONE FRIENDLY

## WARRANTIES

**2 YEAR HEAT PUMP WARRANTY**

**COMPRESSOR GUARANTEED 5 YEARS**

**15 YEAR OLD TITANIUM COIL**

**AGAINST CORROSION**

## ADVANTAGES

- ULTRA COMPACT DESIGN
- COMPATIBLE WITH ALL ABOVE GROUND SWIMMING POOL
- TRANSPORTABLE (18KG)
- ULTRA SILENT
- ECONOMIC
- SECURISED ELECTRICAL SYSTEM
- OPERATING FROM 15°C

Heating power

**2,7kW**

Power  
Consumption  
**0,6kW**

**COP 4.75**

\* COP above 4,75 based on Air 26°C, water 26°C, hygro 80% and certified by TÜV

\*\* Average noise 10m distance from heat pump





## DONNEES TECHNIQUES

Swimming pool volume (m³)	≤ 20	
Référence : PC-NANOPACACTION		
Air 26°C Water 26°C Hygro 80%	Capacity (W)	2750
	Puissance consumption (W)	580
	COP	4,75
Air 15°C Water 26°C Hygro 70%	Capacity (W)	2150
	Puissance consumption (W)	540
	COP	4
Electricity supply	Mono 230V / 50Hz	
Max power (W)	600	
Max current (A)	2,59	
Heating temperature range	15°C / 40°C	
Operating range	10°C / 43°C	
Flow (m³/h)	1,2	
Refrigerant	R32	
Packaging dimensions (mm)	400 x 280 x 365	
Dimensions (mm)	460 x 370 x 415	
Net/gross weight (kg)	17 / 19	
Noise at 1 metre (dB(A))	<50	
Noise at 4 metres (dB(A))	<40	
Noise at 10 metres (dB(A))	<32	
Compressor type	Rotatif	
Compressor make	Toshiba	
Exchanger	Twisted Tech® Titane	
Function	Chauffage	
Load losses (mCE)	0,8	

Standard E.U.  
Certifié T.U.V.

## ACCESSOIRES INCLUS



Free standing  
and tubular  
structure pools



Above ground pools



Small pools of  
less than 20m³





**Commercial service**

Tel : +33 (0)4 91 51 15 16

Mail : [contact@poolstar.fr](mailto:contact@poolstar.fr)

**WWW.POOLEX.FR**